UL Product **iQ**[™]

YDPU2.E225897 - TUBING, EXTRUDED INSULATING - COMPONENT

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

QIFURUI ELECTRONICS CO

1924 W HOLT AVE POMONA, CA 91768-3351 USA

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Not Heat Shrinkable PTFE					
HF	600	200	CL	-	Yes
HF (300V)	300	200	CL	-	Yes
Flexible heat-shrinkable Polyolefin					
QFR-h	600	125	All, except Clear	-	Yes
Not heat shrinkable Polyvinyl Chloride (PVC)					
QFR-PVC-300	300	105	All except black	-	No
QFR-PVC-300 (BK)	300	105	ВК	-	Yes
QFR-PVC-600	600	105	All except black	-	No
QFR-PVC-600 (BK)	600	105	ВК	-	Yes
Not heat shrinkable Silicone rubber (Si)					
QFR-SI-600	600	150	All except clear	-	Yes

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

Marking: Company name or tradename "E225897", catalog designation, inside diameter (before and after recovery for heatshrinkable tubing), voltage rating, temperature rating in degrees celsius and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2018-02-27

(ቢ)

E225897

TUBING, EXTRUDED INSULATING - COMPONENT | UL Product iQ

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"